



**SSGF make Rhomboidal shape Wire Rope Panel 'SSRHOMBUS'**

Sr.No	Description	Dimensions	
<b>A</b>	<b>Standard Panel Mesh Opening</b>		
	- Nominal Mesh Size	250mm X 250mm	
		300mm X 300mm	
		400mm X 400mm	
		450mm X 450mm	
<b>B</b>	<b>Panel Height</b>	Up to 18 meter	
	(Panel size is Nominal +/- 3%)		
<b>C</b>	<b>Panel Width</b>	Up to 6 meter	
	(Panel size is Nominal +/- 3%)		
<b>D</b>	<b>Steel Rope</b>		
	- Rope Type (ISO 2048, EN 12385- 4)	8mm Diameter	10mm & 12mm Diameter
	- Zinc Coating (EN 10264-2)	Class B ; Class A	
	- Rope Grade	1770 N/mm2	
	- Rope Construction	6X7+WC	6X19+WC
	- Minimum Breaking Load	40.7 kN	63.0 kN & 90.7 kN
<b>E</b>	<b>Perimeter Rope (Optional)</b>		
	- Rope Type (ISO 2048, EN 12385- 4)	10,12,14,16mm	
	- Zinc Coating (EN 10264-2)	Class B ; Class A	
	- Rope Grade	1770 N/mm2	
	- Rope Construction	6X19+WC	
<b>F</b>	<b>Clip Details</b>		
	- Material	CRC	
	- Thickness	17SWG (1.42mm)	
<b>G</b>	<b>Knot Tear Resistance (Maximum Breaking Load)</b>	22kN to 24kN	

Office & Plant Address:

GAT No 263, Grampanchayat Milkat No 4413 & 4412, Wadegaon Road, Kesnand,  
Taluka- Haveli, Pune, India- 412207

eMail:

reachus@shrisai-india.com  
reachus@ssgf.in

Phone:

+91 95457 54333  
+91 98902 97265